

Limiting Oxygen Index Chamber

LOI



Stocked, Distributed, and Supported by

SENSORS
INCORPORATED

507 Kelsey Street • Delano, MN 55328
Phone 763-972-1040 Fax 763-972-1041
Toll Free 888-920-0939
Sensorsincorporated.com

Features

- Easy to Operate – User needs only to ignite specimen and adjust gas flow
- Flexible Sample Testing – Specimens may be in rod, film or composite form
- Uniform Combustion Atmosphere – Nitrogen and oxygen are fully mixed in a special dispersion chamber and glass bead bed before entering column
- Precision Gas Flow Metering – Micro-adjustment flowmeters allow precise control of gases
- Conforms to ASTM D2863 and ISO 4589-1, ISO 4589-2
- Twin Gas Flowmeters with Control Needle Valves, Certified Calibration to $\pm 0.5\%$
- Twin Gas Pressure Gages (0 to 100psi)
- Chimney Gas Dispersion Chamber with Glass Bead Bed
- Rigid Specimen Holder

Standard Features

- Twin Gas Flowmeters with Control Needle Valves, Certified Calibration to $\pm 0.5\%$
- Twin Gas Pressure Gages (0 to 100psi)
- Chimney Gas Dispersion Chamber with Glass Bead Bed
- Rigid Specimen Holder

Optional Features

- Smoke Density Measurement System, includes Smoke Density Detector and Chart Recorder – Records variations in smoke generation throughout test (120Vac 60Hz or 230Vac 50Hz)
- Non-rigid Specimen Holder (for film, sheet, etc.)

www.dynisco.com

Description

The advanced LOI Limiting Oxygen Index Chamber accurately determines the relative flammability of plastics and other materials. It conforms to ASTM D2863 and ISO 4589-1, ISO 4589-2 standards and provides a means for safely determining the relative flammability of materials by measuring the minimum

oxygen concentration that will support combustion. The test specimens are burned in a precisely controlled atmosphere of nitrogen and oxygen. The operator adjusts the supply gases and uses the flowmeter readings to calculate the oxygen index.

Specifications

Dimensions	20"H x 12"W x 12.4"D (50.8cm x 30.5cm x 31.5cm)
Weight	32.5 lbs. (14.7kg)
Gas Requirement	Commercial grade or better Nitrogen (N ₂) and Oxygen (O ₂)

All dimensions are in inches (millimeters).

©2008. Dynisco reserves the right to make changes without notice.
Refer to www.dynisco.com for access to Operator Manual and other support documentation.
DDS276071 10.08